

Please provide: ☐ Quotation ☐ Order

Date: _____

Contact Details:

Company Name:

Reference:

Delivery Address:

Postcode:

Name (present for delivery):

Mobile Number:

Main Requirements:

Externally Viewed

Overall Measurement (including any cill, corner post, jamb, add-ons):

Width: _____ mm

Height: _____ mm

Recommended: Allow minimum 10mm tolerance between your overall frame size and your opening size

Opening direction

☐ Outwards* ☐ Inwards

Door Type

☐ Entrance Door (single)

☐ French Doors

Hinged - Entrance Doors:

☐ Left* ☐ Right

Main Access - French Doors:

☐ Left* ☐ Right

Cill (cill height is 25mm and included in overall frame height):

☐ None* ☐ 90mm Stub ☐ 150mm ☐ 190mm ☐ 230mm

Additional 100mm for Cill Horns

☐ Yes* ☐ No - same as overall width ☐ Other _____ mm

Drainage

☐ Face* ☐ Concealed (only with cill)

☐ None (internally used doors only)

Beading

 (supplied unglazed):

☐ 28mm* (for double glazed - pre-gasketed clip in bead)

☐ 36mm (for triple glazed - separate bead and wedge gasket)

Restrictor

 (supplied loose)

☐ x 1 ☐ x 2

Panel/s (see page 2 and/or The Ultimate Door brochure):

☐ Name _____ and quantity _____

☐ Satin* ☐ Clear

☐ Other _____

Configuration:

VIEWED FROM OUTSIDE

Bottom Track Detail

☐ Weather Rated Threshold*

☐ Integrated threshold with 150mm cill^c

☐ 20mm Silver Anodised Low Threshold - NOT Weather Rated

☐ Low Threshold (above) + Silver Anodised Rebate

☐ Low Threshold (above) + Silver Ext. Anodised Convenience Ramp

☐ Low Threshold (above) + Silver Int/Ext. Anodised Convenience Ramp

☐ Low Threshold (above) + Silver Anodised Rebate + Ext. Ramp

Vents and Add-ons

 (trickle vents are only available in white, grey and black)

Vents in sash (1629mm²)^b ☐ 2 ☐ 3 ☐ 4 ☐ 5 ☐ 6 ☐ 7

Vents in 38mm Add-on (3954mm²)^b ☐ 1 ☐ 2 ☐ 3 ☐ 4 ☐ 5 ☐ 6

20mm Add-on ☐ Top ☐ Left ☐ Right

38mm Add-on ☐ Top ☐ Left ☐ Right

Profile Colour/s

☐ White 9016 Gloss ☐ Grey 7016 Matt ☐ Black 9005 Matt

☐ Grey 7016 / White 9016 ☐ Black 9005 / White 9016

☐ Special: External RAL _____ Internal RAL _____

Handle Options:

Main Handle Options

☐ Lever/Lever*

☐ Stainless Steel Brushed Satin Silver Lever/Lever with Split Escutcheon^A

Lever/Lever Handle Colours

☐ White ☐ Grey ☐ Black ☐ Chrome

☐ Grey / White ☐ Black / White ☐ Satin ☐ Gold

Locking Options

☐ 3* Cylinder/s Key / Key* ☐ 3* Cylinder/s Thumb Turn

Hinge Colours

☐ Black* ☐ Grey 7016 ☐ White

Dual Colours and Special Colour Profile - ONLY available in Black

Single Transom 55mm:

Position:

☐ Main Access Door* ☐ Secondary Door ☐ Both

Centre of Transom from base of frame^D _____ mm

Sketch for Transom:

Externally Viewed

☐ Unglazed

☐ Orkney Half Panel

☐ Fetlar Vertical Half Panel



*As standard

^AOnly available in Brushed Satin Silver

^BThe mm² per trickle vent

^COpen out only - not compatible with open in doors

^DMinimum 400mm, Default 850mm if not specified

Style Options:



Size and Weight Restrictions:

Entrance Door	Min	Max
Overall Height:	1800mm	3000mm
Overall Width:	700mm	1300mm

French Doors	Min	Max
Overall Height:	1800mm	3000mm
Overall Width:	1365mm	2400mm

Prior to delivery, The ALUNA Doors will be fully assembled and its operation carefully checked. No responsibility will be accepted unless the doors have been installed fully square, plumb and level, in accordance with the code of practice for the installation of aluminium doors and windows (COP)W362/2. Toe and heeling of the panel is required.

ALL IMAGES ARE FOR ILLUSTRATION PURPOSE ONLY. Actual product positioning, number of slats, may vary due to the dimensions of the door and panel.

Panels - Only sold in unison with the ALUNA Doors. Panels are not sold separately.

All panels require 'toe and heeling' and we recommend glass units are silicone sealed on site.

Options: Standard colour panels are available in Anthracite Grey 7016 Matt, Jet Black 9005 Matt or Traffic White 9016 Gloss, with Glass and Stainless Steel Glazing Frames.

Key:

- *As standard
- ^aOnly available in Brushed Satin Silver
- ^bThe mm² per trickle vent
- ^cOpen out only - not compatible with open in doors
- ^dMinimum 400mm, Default 850mm if not specified

Sliders UK (Doors and Windows) Limited

220 Cocker Road, Walton Summit Centre,

Preston, Lancashire PR5 8BP

T : 01772 698222 E : sales@sliders-uk.com

W : www.sliders-uk.com

