

Please provide: Quotation Order

Date: _____

Contact Details:

Company Name:

Reference:

Delivery Address:

Postcode:

Name (present for delivery):

Mobile Number:

Main Requirements:

Externally Viewed

Opening direction:

Outwards* Inwards

Main Access Door:

Left* Right

Overall Measurement (including any cill / add-ons):

Width: _____ mm

Height: _____ mm

Recommended: Allow minimum 10mm tolerance between your overall frame size and your opening size

Cill (cill height is 25mm and included in overall frame height):

None* Stub 150mm 190mm

Additional 100mm for Cill Horns

Yes* No - same as overall width Other _____ mm

Drainage

Face* Concealed (only with cill)

None (internally used doors only)

Beading (supplied unglazed):

28mm* (for double glazed - pre-gasketed clip in bead)

36mm (for triple glazed - separate bead and wedge gasket)

Panel/s (see The Ultimate Door brochure):

Name _____ and quantity _____

Delivery Options:

Fully assembled - with outer frame joints sealed with silicon

Additional Options:

Bottom Track Detail:

Weather Rated Threshold*

Integrated threshold with 150mm cill

20mm Silver Anodised Low Threshold - NOT Weather Rated

Low Threshold (above) + Silver Anodised Rebate

Low Threshold (above) + Silver Anodised Convenience Ramp

Low Threshold (above) + Silver Anodised Rebate + Ramp

Vents and Add-ons (trickle vents are only available in white, grey and black)

Vents in sash (3000mm²) 1 2

38mm Add-on Top Left Right

Vents in Top Add-on (4000mm²) 1 2

Colour/s

White 9016 Gloss Grey 7016 Matt Black 9005 Matt

Grey 7016 / White 9016 Black 9005 / White 9016

Special: External RAL _____ Internal RAL _____

Main Handle Option

Lever/Lever* Lever/Lever with Split Escutcheon^A

Lever / Lever Handle Colours

White Grey Black Chrome

Grey / White Black / White Satin

Hinge Colours

Black* Grey 7016 White

Dual Colours and Special Colours - ONLY available in Black

Single Transom 55mm:

Position:

Main Access Door* Secondary Door Both

Centre of Transom from base of frame^B _____ mm


Sketch for Transom:

Externally Viewed

1/2 Panel

Orkney

Fetlar - Vertical



Notes:

Sliders UK (Doors and Windows) Limited
Unit 232, Oldfield Road, Walton Summit,
Bamber Bridge, Lancashire PR5 8BG
T : 01772 698222 E : sales@sliders-uk.com
W : www.sliders-uk.com

*As standard

^A Only available in Brushed Satin Silver

^B Minimum 400mm, Default 850mm if not specified

PLEASE NOTE: Adjustable Jambes are standard with EVO French Doors



Features and Benefits:

- Maximum height 2400mm (with lock extension)
- Maximum width 1200mm
- Maximum sash weight 120kg
- Stock colours (White, Grey, Grey on White, Black and Black on White) on short reliable lead times
- Dual Colour & Special Finishes available
- Qualicoat "Seaside" powder coating specification as standard
- Opening either in or out
- Low threshold options
- 30mm polyamide thermal break for increased thermal values

Size and Weight Restrictions:

French Doors	Min	Max
Overall Width:	1365mm	2400mm
Overall Height:	1800mm	3000mm
Panel Width:	600mm	1200mm
Weight Per Panel:		120kg

Additional Information:

Prior to delivery, The Ultimate EVO Entrance Doors will be fully assembled and its operation carefully checked. No responsibility will be accepted unless the doors have been installed fully square, plumb and level, in accordance with the code of practice for the installation of aluminium doors and windows (COP)W362/2. Toe and heeling of the panel is required.

ALL IMAGES ARE FOR ILLUSTRATION PURPOSE ONLY. Actual product positioning, number of slats, may vary due to the dimensions of the door and panel.

Panels - Only sold in unison with the Evo Aluminium Entrance Doors, French Doors and Side Frames. Panels are not sold separately.

All panels require 'toe and heeling' and we recommend satin glass units are silicone sealed on site.

Options: Standard colour panels are available in Anthracite Grey 7016 Matt, Jet Black 9005 Matt or Traffic White 9016 Gloss, with Satin Glass and Stainless Steel Glazing Frames.

Key:

* As standard

^A Only available in Brushed Satin Silver

^B Minimum 400mm, Default 850mm if not specified

Sliders UK (Doors and Windows) Limited
Unit 232, Oldfield Road, Walton Summit,
Bamber Bridge, Lancashire PR5 8BG
T : 01772 698222 E : sales@sliders-uk.com
W : www.sliders-uk.com

