



Please provide: Quotation Order	Date:	
Contact Details:	Additional Options:	
Company Name:	Bottom Track Detail:	
	☐ Weather Rated Threshold*	
Reference:	☐ Integrated threshold with 150mm cill	
	☐ 20mm Silver Anodised Low Threshold - NOT Weather Rated	
Delivery Address:	☐ Low Threshold (above) + Silver Anodised Rebate	
Delivery Address.	☐ Low Threshold (above) + Silver Anodised Convenience Ramp	
	☐ Low Threshold (above) + Silver Anodised Rebate + Ramp	
	Vents and Add-ons (trickle vents are only available in white, grey and black)	
Postcode:	Vents in sash (3000mm²) ☐ 1 ☐ 2	
	38mm Add-on ☐ Top ☐ Left ☐ Right	
	Vents in Top Add-on (4000mm²) ☐ 1 ☐ 2	
Name (present for delivery):	Colour/s	
	☐ White 9016 Gloss ☐ Grey 7016 Matt ☐ Black 9005 Matt	
Mobile Number:	☐ Grey 7016 / White 9016 ☐ Black 9005 / White 9016	
	Special: External RAL Internal RAL	
Main Requirements:	Main Handle Option	
Externally Viewed	☐ Lever/Lever* ☐ Lever/Lever with Split Escutcheon ^A	
Opening direction:	Lever / Lever Handle Colours	
☐ Inwards* ☐ Outwards	☐ White ☐ Grey ☐ Black ☐ Chrome	
Hinged:	☐ Grey / White ☐ Black / White ☐ Satin	
☐ Left* ☐ Right	Hinge Colours	
Overall Measurement (including any cill / add-ons):	☐ Black* ☐ Grey 7016 ☐ White	
Width: mm	Dual Colours and Special Colours - ONLY available in Black	
Height: mm	Single Transom 55mm:	
Recommended: Allow minimum 10mm tolerance between your overall frame size and your opening size	Position:	
Cill (cill height is 25mm and included in overall frame height):	Centre of Transom from base of frame ^B mm	
□ None* □ Stub □ 150mm □ 190mm	Sketch for Transom: Externally Viewed 1/2 Panel	
Additional 100mm for Cill Horns		
☐ Yes* ☐ No - same as overall width ☐ Othermm		
Drainage	□ Orkney	
☐ Face* ☐ Concealed (only with cill)	□ Fetlar - Vertical e.g. 900mm	
☐ None (internally used doors only)	Ţ	
Beading (supplied unglazed):	Notes:	
28mm* (for double glazed - pre-gasketed clip in bead)		
☐ 36mm (for triple glazed - separate bead and wedge gasket)		
Panel/s (see page 2 and/or The Ultimate Door brochure):		
☐ Name and quantity	Sliders UK (Doors and Windows) Limited	
Delivery Options:	Unit 232, Oldfield Road, Walton Summit	

^A Only available in Brushed Satin Silver

^B Minimum 400mm, Default 850mm if not specified

 $\ensuremath{\ensuremath{\square}}\xspace$ Fully assembled - with outer frame joints sealed with silicon

Unit 232, Oldfield Road, Walton Summit, Bamber Bridge, Lancashire PR5 8BG

T:01772 698222 E:sales@sliders-uk.com

W: www.sliders-uk.com











Style Options:















Hoy



Islay

Fetler Horizontal

Fetler Vertical









Jura

Lismore

Lundy

Orkney

Rum













Sanday

Scalpay Shetland

Stronsay





Single Door	Min	Max
Height	1800mm	3000mm
Width:	700mm	1300mm

Additional Information:

Prior to delivery, The Ultimate EVO Entrance Doors will be fully assembled and its operation carefully checked. No responsibility will be accepted unless the doors have been installed fully square, plumb and level, in accordance with the code of practice for the installation of aluminium doors and windows (COP)W362/2. Toe and heeling of the panel is required.

ALL IMAGES ARE FOR ILLUSTRATION PURPOSE ONLY. Actual product positioning, number of slats, may vary due to the dimensions of the door and panel.

Panels - Only sold in unison with the Evo Aluminium Entrance Doors and French Doors. Panels are not sold separately.

All panels require 'toe and heeling' and we recommend clear or satin glass units are silicone sealed on site.

Options: Standard colour panels are available in Anthracite Grey 7016 Matt, Jet Black 9005 Matt or Traffic White 9016 Gloss, with Satin Glass and Stainless Steel Glazing Frames.

Key:

- * As standard
- A Only available in Brushed Satin Silver
- ^B Minimum 400mm, Default 850mm if not specified

Sliders UK (Doors and Windows) Limited Unit 232, Oldfield Road, Walton Summit, Bamber Bridge, Lancashire PR5 8BG

W: www.sliders-uk.com





T:01772 698222 E:sales@sliders-uk.com



